


**LOAD CELL, AND CRANE OVERTURN ALARMING DEVICE**

**Patent number:** JP2001220086  
**Publication date:** 2001-08-14  
**Inventor:** SAITO FUMIHIRO; KAMINOHARA MOTOYASU;  
 KOBAYASHI SEIJI  
**Applicant:** FURUKAWA CO LTD  
**Classification:**  
 - international: **G01L1/22; B66C13/16; B66C23/78; G01L1/26;**  
**G01L1/20; B66C13/00; B66C23/00; G01L1/26; (IPC1-**  
**7): B66C13/16; B66C23/78; G01L1/22; G01L1/26**  
 - european:  
**Application number:** JP20000226337 20000727  
**Priority number(s):** JP20000226337 20000727; JP19990344528 19991203

Report a data error here

**Abstract of JP2001220086**

**PROBLEM TO BE SOLVED:** To improve the alarming accuracy of an overturn alarming device by detecting the low load of an outrigger with high accuracy. **SOLUTION:** This crane overturn alarming device comprises a load cell 1 which comprises a coil spring 5 having a strain gage 4, and an upper load cell case 6 and a lower load cell case 7 which holds the coil spring 5 from the top and the bottom thereof to transmit the load of the outrigger to the coil spring 5, and is provided with support parts 8, 9 to support the load exceeding a predetermined value to restrict the deflection of the coil spring 5 between the upper load cell case 6 and the lower load cell case 7, and an alarm unit to give the overturn alarm based on the detected load of the outrigger from the load cell 1.



Data supplied from the esp@cenet database - Worldwide